

95. (new) The lockset drilling guide of claim 93, wherein said spacing tab is permanently attached to said frame.

<sup>96</sup>

~~94~~. (new) The lockset drilling guide of claim 92, wherein said frame is secured to the door by fasteners engaging the door edge.

<sup>97</sup>

~~95~~. (new) The lockset drilling guide of claim 92, wherein said first flange defines a mounting opening, said mounting opening used to secure the frame to the door.

<sup>98</sup>

~~96~~. (new) The lockset drilling guide of claim <sup>97</sup>~~95~~, wherein the mounting opening is located on the first flange so as to align with an opening on latch plate that is part of the lockset.

97. (canceled) *Never existed. Proposed in interview of 10-18-04. DH.*

<sup>99</sup>

~~98~~. (new) A lockset drilling guide for a door having a first planar face and a second planar face that is perpendicular to said first planar face, comprising:

a frame defining an opening in said frame, said frame comprising a first flange that lies adjacent to and parallel to said first face of said door and a second flange mounted perpendicularly thereto and lying adjacent to and parallel to said second face, said opening being on said second flange; and

a positioning member attached on said first flange by a flexible piece, said positioning member being movable from a first position located between the first flange and the first face of said door to a second position not between the first flange and first face of said door;

wherein said positioning member laterally displaces said opening on said second face when said positioning member is moved from said first position to said second position.